

POLARZONE NORTHWEST Hydrotherapy Spas

TEL	
1	.877.765.2796
FAX	
	425.746.2133
DIRE	СТ
	425.830.6484



POLARZONE PRO PLUS

DIMENSIONS LENGTH: 108" WIDTH: 86" HEIGHT: 35"

Polarzone Spas are self contained and portable.

FLOOR REQUIREMENTS: 65 sq. ft.

CAPACITY: 425 Gallons, Up to 7 Athletes

DRY WEIGHT: 1600 lbs. **FILLED WEIGHT:** 5145 lbs. (Approx. 79 lbs. per sq. ft)

ROOM HEAT GAIN: Cryotherapy Spa Air Cooled Condenser Approx. 25,000 BTU/HR Ambient Heat Gain. Hot Therapy Spa 5000 BTU/HR Ambient Heat Gain. Condenser air inlet either on left or right hand side. Air outlet at front of spa.

Polarzone reserves the right to change, revise, delete or cease information posted

POLARZONE NW LLC - PO BOX 6473 - BELLEVUE WA 98008-0473

FEATURES

• Polarzone Hydrotherapy spas are completely "Self Contained" and custom manufactured for each client, using your team/company colors, and incorporating state of the art technology, components, and materials. Polarzone spas provide superior performance and reliability along with installation and maintenance cost savings. All that is needed for installation is spa wiring hook up!

• Computerized Deluxe Digital controls feature a user friendly touch key pad that Provides exact control of hydrotherapy spa water temperature and programmable filtration cycles.

• Polarzone spas feature our exclusive **Triple Hurdle Sanitation System**[™] that has been proven to effectively address the control of all infectious disease pathogens in the spa water - including **MRSA**, **VRE**, **E. Coli**, and **Athletes Foot Fungus**. <u>THSS</u>[™] is a three-tier water sanitation process that includes Ultraviolet Light Sterilization, Ozone Injection, and Automated Bromine Infusion. In addition, our spas have a highly efficient filtration system and the shells are manufactured with the antimicrobial Microban® additive. Microban® helps prevent the growth of microbes within the spa shell and on its surface. Your Polarzone spa will keep your Staff and Athletes safe, providing sparkling clean water even under heavy use.

• Polarzone spas have a unique overflow control system -The spa refills itself. No need to top-off after large water displacement, saving water and chemical costs.

• Polarzone spa shells are custom manufactured incorporating extra thick fiberglass and a support structure for those heavy athletes.

• Optional Novar "online" Direct Digital Control system blends with existing building energy management systems providing your maintenance staff, and Polarzone, with internet monitoring of all functions of your spa. Please visit our website at <u>www.polarzone-nw.com</u> for all of the exciting features that come as standard equipment on all Polarzone Hydrotherapy Spas.

POWER REQUIREMENTS One 2 pole 208/230 VAC 50 amp circuit with a neutral and ground.